



Power [kW]	Duty Cycle	Base speed [rpm]	Base freq. [Hz]	Base voltage Δ [V]	Base voltage Y [V]	Protection	Ins. Cl.
6.0	S1	18000	300	220	380	IP54	F
Min speed [rpm]		Max speed [rpm]	Max freq. [Hz]	Absorb. Δ [A]	Absorb. Y [A]	Part number on nameplate	
6000		24000	400	21.8	12.6	COM51600438	
Balancing according to ISO 1940 - G2.5 @ 24000 rpm		Balancing type		tool type full key	tool type half key	Peso / weight	
						10.52 kg	
Tolleranze non quotate: UNI EN 22768 fH Smussi non quotati: 0.5mm				$\nabla = 0.8 \nabla$	$\nabla = 3.2 \nabla$	$\nabla = 12.5 \nabla$	$\sim = \nabla$
rev. n°	description			date	signature	Customer	
00	Emissione			26/06/2018	D. Bottarel	Catalogo	
						Drawing code	
						COM51600438	
drawn - date	approved - date	checked - date	sostituisce il		foglio / sheet	scala	
D. Bottarel - 26/06/2018	S. Perli - 26/06/2018	S. Perli - 26/06/2018	sostituito dal		1 / 1	n.d.	

TEKNOMOTOR

Teknomotor S.r.l.
Via Argenegea 31, I-32038 Quero Vas (BL)
www.teknomotor.com

Title
5160-D-2DB-P-ER32-HY-HD-RR-RH

Customer
Catalogo

Drawing code
COM51600438

foglio / sheet
1 / 1

scala
n.d.



A4